


204.95 EUR

incl. 19% VAT, plus [shipping](#)



- INTEL® Pine Trail-D Processor D525+ ICH8M Chipset
- Support 1 * DDR3 667/800MHz Single CH up to 2GB
- 3. Support 1 * Serial ATAI (3Gb/s) Devices
- 1 * 18 bits Single Channel LVDS header
- Supports 4 * Realtek RT8111EVL Gigabit LAN
- Provides 2 * Mini PCI-E socket (one support mSATA card)
- Provides 1 * CF card socket (can support both CF card & CF SATA card)
- Provides 1 * SIM card socket (optional)
- Provides front I/O card for 4 * LAN LED indicators
- Support CPU Smart FAN
- Compliance with ErP standard
- 148 x 102mm 3.5" SBC Form Factor

CPU	INTEL® Pine Trail-D Processor D525 (1.86GHz)
Chipset	INTEL® ICH8M Express chipset
Memory	1 * DDR3 667/800MHz Single CH SO-DIMM up to 2GB
Expansion Slots	2 * full size Mini PCI-E
Storage	1 * Serial ATAI 3Gb/s connectors 1 * mSATA socket (Share with one of Mini PCI-E socket)
Audio	N/A
Ethernet LAN	4 * RTL8111E PCI-EVL Gigabit LAN
USB	Embedded 6 * USB 2.0/1.1
LVDS	Onboard 1 * 18-bits Single CH LVDS connectors
Rear Panel I / O	2 * USB 2.0/1.1 ports 1 * COM port 4 * RJ-45 ports 1 * 12V DC-IN JACK

Internal I / O	2 * USB 2.0 header for 4 * USB 2.0 ports 1 * VGA header 1 * COM header (COM2 for RS232/422/485) 1 * GPIO header 1 * CIR header System/Chassis/NB Fan Connectors 1 * CF card socket (can support both CF card & CF SATA card) DIY switch x2 (reset & power button)
BIOS	AMI 8MB DIP Flash ROM
Form Factor	3.5" SBC form factor (148mmx102mm)
Certificate	CE,FCC,RoHS,ERP
Functional	Networking Appliance
Temperature	Operating within 0~60 centigrade Storage within -20-85 centigrade

Product Accessories

- Front I/O card
- Front panel cable
- NIC LED cable
- USB cable
- Manual
- CD
- 1x SATA cable
- SATA power cable