



429.00 EUR

incl. 19% VAT, plus [shipping](#)

- For Celeron-M/Pentium-M
- Integr. Automotive PSU
- Dualchannel VGA
- PCMCIA

CARTFT.COM

Support:  [Assembling Tutorial \[DE\]](#) |  [Assembling Tutorial \[EN\]](#) |  [Dual-Out-HowTo \[EN\]](#)

The CALU-M(2)C-Series has an integrated car-power supply (direct connectable to car battery and ignition plus + integrated automatic Start/Stop-Controller.

The time intervals for automatic Start and Stop can be adjusted in the BIOS of the PC !

As an additional highlight this barebone offers a PCMCIA slot.

CALU specifications

Processor (supported)	Intel Pentium M processor or Celeron M processor (Dothan or Banias) 1.3GHz or higher
Memory	Supports DDR 400/333/266 DIMM RAM 0.8" low profile 2x memory slots ! Maximum : 2 GB
Video	Intel Extreme Graphics 2 Supports up to 64MB DVM T video memory
Audio	Software AC '97 Audio CODEC
Peripheral Connection	Front : 1 x PCMCIA Slot 1 x IEEE 1394 Firewire port 1 x MIC Port 1 x Ear Phone output Jack Power-on button Reset button Power-on and HDD LED Rear : 1 x RS232 COM port 1 x RJ45 10/100Mb Fast Ethernet 1 x Line-Out output Jack 2 x USB 2.0 / 1.1 Ports 1 x 15 pin VGA 1 x DVI
Storage	One 2.5 inch Hard Disk and 9.5mm high. (Support Ultra DMA 33/66/100).
Weight & Size	System approximately 3kg (fully equipped). System Dimension: 155 x 255 x 55 mm
Power req.	9-16V, 5A

Accessory

Storage	Supports all 2.5" standard IDE hard drive, ATA-100/66/33.
Scope of supply	Connector cable for Plus, ignition plus and ground
	Barebone
	CPU Kühlkörper

Installation Tutorial : [Support / Manuals](#)

Graphics driver for 800x480 resolution : [Here](#)