

198.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Pico-ITX
- SATA
- DDR-II !
- 1 Ghz CPU



|                      |  |
|----------------------|--|
| <b>Model</b>         | VIA EPIA PX1000G   |
| <b>Processor</b>     | VIA C7 1.0 GHz - Socket Nano25G4   |
| <b>Chipset</b>       | VIA V3700 Unified Digital Media GSP Chipset  |
| <b>System Memory</b> | 1 DDR2 512 3200MHz module<br>Up to 1GB memory size   |
| <b>GPU</b>           | Integrated VIA UniChrome Pro3 3200G GSP graphics<br>with MPEG-2/4 and WMV9 decoding acceleration |

|                         |   |
|-------------------------|---|
| Onboard IDE             | 1 SATA/IDE 133/100MHz connector (2.0mm 44-pin header)   |
| Onboard Serial ATA      | 1 SATA connector  |
| Onboard LAN             | 1 VIA VT6102G 10/100Mbps Ethernet controller<br><br>with Power Managemen System   |
| Onboard Audio           | VIA VT1708A High Definition Audio Codec   |
| Internal I/O Connectors | <p>4 USB pin headers for 4 USB 2.0 ports</p> <ul style="list-style-type: none"> <li>• 1 COM port connector</li> <li>• 1 PS2 mouse/keyboard pin header</li> <li>• 1 LVDS/DVI connector</li> <li>• 1 Multimedia connector to support external TV-out interface, Video capture port interface and Low pin count interface</li> <li>• 1 Audio pin header for line-out, line-in, mic-in, S/PDIF in, and 7.1 channels audio output</li> <li>• 1 Fan pin header for CPU fan</li> <li>• 1 Pico-ITX power connector</li> </ul> |
| External I/O Ports      | <p>1 RJ-45 LAN port</p> <ul style="list-style-type: none"> <li>• 1 VGA port</li> </ul>  |
| BIOS                    | <p>Award BIOS</p> <ul style="list-style-type: none"> <li>• 4/8Mbit flash memory</li> </ul>  |
| Management              | <p>CPU temperature reading (manufacturing option)</p> <ul style="list-style-type: none"> <li>• Watch Dog Timer (manufacturing option)</li> <li>• Keyboard-Power-on, Timer-Power-on</li> <li>• Wake-on-LAN</li> <li>• System power management</li> <li>• AC power failure recovery</li> </ul>  |
| Operating Temperature   | 0°C - 50°C  |
| Operating Humidity      | 0% - 95% (relative humidity, non-condensing)  |
| Form Factor             | • Pico-ITX 10 cm x 7.2 cm   |